



THOR Tarp

DIV. OF

ODIN

INTERNATIONAL, INC



ThoroWeave 700 Mesh

Bright Safety Yellow Runway Closure Markers

Specification Sheet

VINYL COATED MESH

11 x 11 count per square inch multi-fibrous high tenacity rip-stop polyester tire cord open vinyl coated mesh. 10 ounce per square yard total weight composed of 3 oz/sy PET thread and 7 oz/sy traffic yellow vinyl coating resulting in a 70% closed mesh construction allowing water to flow through.

PHYSICAL PROPERTY CHART

<u>Property Tested</u>	<u>Test Method</u>	<u>Value</u>
Weight	Available on Request	10 oz/sy
Tongue Tear	ASTM D 2261	45#'s Warp 45#'s Weft
Grab Tensile	ASTM D 1682	235#'s Warp 235#'s Weft
Strip Tensile	ASTM D 1682	200#'s Warp 200#'s Weft
Cold Crack Weathering	ASTM D 750	-40 ° F > 2500 hours
Mullen Burst	ASTM D 3786	250 psi
Water Absorption	ASTM D 471	<5% gain for 7 days @ 160 °F

Marker Construction: Double needle lock-stitched triple folded 2" wide hems sewn with UVI stabilized Bonded Polyester #138 Thread with #3 brass rolled rim spur grommets @ 30" centers around entire perimeter.

CORPORATE HQ: P.O. Box 811 • OCONOMOWOC, WI 53066-0811 • 262-569-7171 • FAX: 262-569-1511
TOLL FREE: 1-888-ODIN-INC • 1-888-634-6462 • EMAIL: INFO@THORTARP.COM

WWW.THORTARP.COM