



THOR Tarp

DIV. OF **ODIN** INTERNATIONAL, INC



DuraShield 10,000 Translucent

4-Ply Woven Reinforced Polyethylene

DESCRIPTION

A premium coated fabric with enhanced UV protection for use in garage, specialized cover, and other applications demanding superior performance.

COUNT

Nominal 10 x 10 tapes/inch (38 x 38 tapes/10 cm)

WEIGHT

6.4 oz per square yard (215 gsm)

TENSILE STRENGTH (Grab Method)

Warp - 210 lbs (930 N) ASTM D751 (Meth. A)
Weft - 200 lbs (890 N)

TEAR STRENGTH (Tongue Method)

Warp - 80 lbs (354 N) ASTM D751 (Meth. B)
Weft - 80 lbs (354 N)

MULLEN BURST

440 psi (3046 kPa) ASTM D751

COATING THICKNESS

1.75 mil average (44 micron), 2 sides

SCRIM TYPE

Clear tapes, UV stabilized

COLOR

Clear and colored coating available

ACCELERATED WEATHERING/UV

UV stabilizers added for outdoor performance allow no visible deterioration and typically 70% to 100% strength retention after 2000 hours accelerated weathering exposure. ASTM G53-84

(Q.U.V.[A-340 Lamps] 8 hrs UV @ 60° C/4 hrs condensation % 50° C)

WIDTH

Up to 144 inches

Difficulties may be experienced in heat sealing this material because of the high additive content.

To the best of our knowledge, the information contained herein is accurate. The information provided is based upon data furnished by our suppliers. However, ODIN International, Inc. assumes no liability whatsoever for the accuracy or completeness of the information contained herein. While believed to be reliable, the information of products are intended for use by skilled persons at their own risk. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that those are the only hazards that exist.

CORPORATE HQ: P.O. Box 811 • OCONOMOWOC, WI 53066-0811 • 262-569-7171 • FAX: 262-569-1511
TOLL FREE: 1-888-ODIN-INC • 1-888-634-6462 • EMAIL: INFO@THORTARP.COM

WWW.THORTARP.COM