



THOR Tarp

DIV. OF **ODIN** INTERNATIONAL, INC



DuraShield 11,000 Fire Retardant

Material Composition:	3-ply woven coated polypropylene	
Property	Test	Value
UV Resistance	ASTM D-4355	80% @ 400 hours
Color		White
Weight		6.7 oz/sy
Burst Strength	ASTM D-3786	550 psi
Tensile Strength	ASTM D-1692	Warp: 440 lbs. Fill: 380 lbs.
Thread Count		16.7 x 12.5 psi
Construction:	Seams and hems are double needle lock-stitched and reinforced with 1.5" wide polypropylene webbing, perimeter is finished with brass #4 grommets (1/2"ID) at 2' centers	
Fire Retardancy	ASTM D4372	pass
	NFPA 701 Large Scale	pass
	NFPA 701 Small Scale	pass
	CPAI Spec. 84 - 6	pass
	CPAI Spec. 84 - 7	pass
	Fed Std. 191, method 5903	pass
	ANSI 45.2.2 (Nuclear)	pass

CORPORATE HQ: P.O. BOX 811 • OCONOMOWOC, WI 53066-0811 • 262-569-7171 • FAX: 262-569-1511
TOLL FREE: 1-888-ODIN-INC • 1-888-634-6462 • EMAIL: INFO@THORTARP.COM

WWW.THORTARP.COM