



THOR Tarp
Div. Of **ODIN** International, Inc



SPECIFICATION SHEET

20 MIL FR PVC

GAUGE:	20 MIL	FINISH:	DOUBLE POLISHED
HAND:	3S	COLOR:	CLEAR
WIDTH:	VARIOUS		

TENSILE STRENGTH: ASTM D-882	MD	2900 - 3500 PSI
	TD	260 – 300 PSI
ELONGATION: ASTM D-882	MD	270 – 310 %
	TD	260 – 300 %
100% MODULUS: ASTM D-882	MD	1,550 – 1,950 PSI
	TD	1,800 – 2,200 PSI

FILM CHARACTERISTICS:

Formulated to meet -20°F Cold Impact testing.
Formulated to meet The California State Fire Marshall requirements.
Formulated to meet CPAI-84 requirements.

To the best of our knowledge, the information contained herein is accurate. The information provided is based upon data furnished by our suppliers. However, *ODIN International, Inc.* assumes no liability whatsoever for the accuracy or completeness of the information contained herein. While believed to be reliable, the information of products are intended for use by skilled persons at their own risk. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

CORPORATE HQ: P.O. Box 811 • OCONOMOWOC, WI 53066-0811 • 262-569-7171 • FAX: 262-569-1511
TOLL FREE: 1-888-ODIN-INC • 1-888-634-6462 • EMAIL: INFO@THORTARP.COM

WWW.THORTARP.COM