



THOR Tarp

DIV. OF **ODIN** INTERNATIONAL, INC



WeldView Transparent Colored Welding Screens

WELDVIEW 14 MIL PVC SPEC SHEET as seen at www.Welding-Screens.com

Thickness	14 MIL +/- 5%
Width	66" + 1/4" -0"
Length	101 Yards
Net Weight	150 lbs. +/- 3%
Yard Yield	.67
Finish	Double Polished
Hand	Soft – 3S
Color	Tinted

- **WELD SCREEN MATERIAL**
- **COMPLIANT WITH CALIFORNIA FIRE MARSHAL**
- **UV STABILIZED**
- **-10° F. COLD CRACK**

TENSILE STRENGTH (psi)	MD	2700	ASTM-D-882
	CD	2550	
ELONGATION (%)	MD	240	ASTM-D-882
TEAR STRENGTH (LBS./IN)	MD	330	ASTM-D-1004
	CD	330	
HEAT SHRINKAGE (%)	MD	-5	ASTM-D-1004
	CD	+2	

To the best of our knowledge, the information contained herein is accurate. The information provided is based upon data furnished by our suppliers. However, *ODIN International, Inc.* assumes no liability whatsoever for the accuracy or completeness of the information contained herein. While believed to be reliable, the information of products are intended for use by skilled persons at their own risk. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

CORPORATE HQ: P.O. Box 811 • OCONOMOWOC, WI 53066-0811 • 262-569-7171 • FAX: 262-569-1511
TOLL FREE: 1-888-ODIN-INC • 1-888-634-6462 • EMAIL: INFO@THORTARP.COM

WWW.THORTARP.COM