



THOR Tarp
DIV. OF **ODIN** INTERNATIONAL, INC



DuraShield 3000 FR

Fire Retardant Woven, Coated Polyethylene

DESCRIPTION	Premium flame retardant coated fabrics for industrial and construction applications.		
COUNT	Nominal 5 x 4 tapes/inch		
WEIGH	3.0 oz per square yard (100 gsm) \pm 10%		
TENSILE STRENGTH (Grab Method)	Warp - 75 lbs	ASTM D751 (Meth. A)	
	Weft - 65 lbs		
TEAR STRENGTH (Trapezoidal Method)	Warp - 32 lbs	ASTM D4533	
	Weft - 32 lbs		
MULLEN BURST	130 psi	ASTM D751	
<p>The above physical test results are representative data collected from a number of production runs. Results for an individual roll (based on at least three specimens) may vary from the average by \pm 10%.</p>			
COATING THICKNESS	1.3 mil average, two sides 30 gsm average, two sides		
SCRIM TYPE	Clear tapes		

Conforms to NFPA 701, CPAI-84 sections 6 & 7, Boston Fire Marshall's Test, and California Fire Code

CORPORATE HQ: P.O. Box 811 • OCONOMOWOC, WI 53066-0811 • 262-569-7171 • FAX: 262-569-1511
TOLL FREE: 1-888-ODIN-INC • 1-888-634-6462 • EMAIL: INFO@THORTARP.COM

WWW.THORTARP.COM