



THOR Tarp

Div. OF

ODIN

INTERNATIONAL, INC



ThoroShield™ 2250 FR **Fire Retardant Vinyl Coated Polyester** *“Exceeds the Standard of the Industry”*

- High Strength, Nylon Reinforced, UV stabilized, Coated Vinyl Sheeting
- Standard weight of 22 ounces per square yard (others available)
- Standard thickness of 37 mils (0.037”)
- Stiff walled construction keeps the cover flat
- Easily cleaned with soap, water and mild bleach solution
- Oil and chemical resistant for spills and grease tracking
- Anti-bacterial, anti-fungal, rot and mildew resistant
- 525 pounds of tensile break strength per inch of width
- Hydrostatic Resistance (method ASTM D-3786) of 700 psi
- Remains flexible even after many years of use; waterproof
- Manufactured in the U.S.A. (tolerances are -0/+2”)
- NFPA 701 Certified Fire Retardant Meets All Building Codes
- California Fire Marshal F-121.2
- UL-214 classified
- ASTM E-84, Class A
- MVSS 302
- CPAI 84 Large & Small Index FR
- Stock Color Choices: Gray, Tan, Royal Blue, Forest Green, Black, & White
- Custom Color Choices: Sky Blue, Brown, Maroon, Orange, Red, & Yellow

Visit our website at www.ThorTarp.com, email to info@ThorTarp.com, fax to 1-262-569-1511 or call us at 1-888-634-6462. Thousands of happy customers later, we are committed to your satisfaction!

THOR Tarp Division of ODIN International, Inc.
PO Box 811, Oconomowoc, WI 53066-0811
ThorTarp.com TF:888-634-6462 P:262-569-7171 F:262-569-1511